

Construction limit values

Configuration variants	Minimum order width	Maximum order width	Maximum order height	Maximum order area
Drive variants				
Basic motor type ZM REA	720 mm			
Short motor	646 mm			
Short motor with shortened shaft core	554 mm			
Box + Fabric qualities				
Size 90 + Screen fabric 4 % / 5 % / Screen fabric 1 %		2500 mm	3000 mm	7,5 m ²
Size 90 + Soltis Veozip		2500 mm	2500 mm	6,25 m ²
Size 90 + Soltis 92		2500 mm	3000 mm	7,5 m ²
Size 90 + Soltis B92 / Screen fabric 0 %		2500 mm	2500 mm	5,0 m ²
Size 90 + Twilight		2500 mm	3000 mm	7,5 m ²
Size 110 + Screen fabric 4 % / 5 % / Screen fabric 1 %		3000 mm	3000 mm	9,0 m ²
Size 110 + Screen fabric 4 % / 5 % / Screen fabric 1 %		4000 mm	2300 mm	9,2 m ²
Size 110 + Soltis Veozip		3000 mm	3000 mm	9 m ²
Size 110 + Soltis 92		3000 mm	3000 mm	9 m ²
Size 110 + Soltis B92 / Screen fabric 0 %		2500 mm	3000 mm	7,5 m ²
Size 110 + Twilight		3000 mm	3000 mm	9 m ²
Size 110 + WAREMA SecuTex fabric A2		3000 mm	3000 mm	9 m ²
Size 130 + Screen fabric 4 % / 5 % / Screen fabric 1 %		4000 mm	4500 mm	18 m ²
Size 130 + Screen fabric 4 % / 5 % / Screen fabric 1 %		4500 mm	2300 mm	10,35 m ²
Size 130 + Soltis Veozip		4000 mm	4000 mm	16 m ²
Size 130 + Soltis Veozip		4500 mm	2300 mm	10,35 m ²
Size 130 + Soltis 92		4000 mm	4500 mm	18 m ²
Size 130 + Soltis B92 / Screen fabric 0 %		3500 mm	4500 mm	15,75 m ²
Size 130 + Twilight		4000 mm	4000 mm	16 m ²
Size 130 + WAREMA SecuTex fabric A2		3500 mm	4200 mm	14,7 m ²
Size 150 + Screen fabric 4 % / 5 % / Screen fabric 1 %		6000 mm	6000 mm	18 m ²
Size 150 + Soltis Veozip		6000 mm	5000 mm	18 m ²
Size 150 + Soltis 92		4000 mm	6000 mm	18 m ²
Size 150 + Soltis B92 / Screen fabric 0 %		3500 mm	5500 mm	18 m ²
Size 150 + Twilight		6000 mm	6000 mm	18 m ²
Size 150 + Wear-resistant gauze (design 47005)		6000 mm	3000 mm	18 m ²

Planning

Basic awning

Awning window systems

Front-mounted awnings

Top-mounted awnings

Shaft awnings

Supplementary accessories

Components

Drive variants

Standards